

Description

MS16562-256 Spring Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16562256
Minimum Qty (MOQ):	10
NSN:	5315-00-753-3895
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N MS16562-256 Specifications

Overall Length:	1.980 Inches Minimum And 2.020 Inches Maximum
Diameter:	0.258 Inches Minimum And 0.264 Inches Maximum
Material Thickness:	0.048 Inches Nominal
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-256> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.