

Description

MS16562-265 Spring Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS16562265
Minimum Qty (MOQ):	20
NSN:	5315-00-526-2742
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16562-265 Specifications

Overall Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Diameter:	0.385 Inches Minimum And 0.392 Inches Maximum
Material Thickness:	0.077 Inches Nominal
Hardness Rating:	43.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Shear Strength:	17000 Double Pound
Material:	Steel Comp 410 Overall Or Steel Comp 420 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-265> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.