

Description

length: 5/8", diameter: 3/32", tubular slotted, carbon steel, MS16562 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS1656227 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5315-00-844-3956 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS16562-27 Specifications

| | |
|---|--|
| Overall Length: | 0.610 Inches Minimum And 0.640 Inches Maximum |
| Diameter: | 0.099 Inches Minimum And 0.103 Inches Maximum |
| Material Thickness: | 0.022 Inches Minimum |
| End Item Identification: | W/s:ssbn Mk-118 Fire Control Sys; Helicopter, Carrier Based Asw, Sh-60f; Consolidated Targets; Trainer, B-1b Aircraft; Helicopter, Mh-53e; Missile, Strategic Air To Ground (sram li); Boilers, 1200 Psi; Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Advance Attack, Ah-1w |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Shear Strength: | 1000 Double Pound |
| Material: | Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Slotted |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.