

Description

length: 5/8", diameter: 3/32", tubular slotted, carbon steel, MS16562 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1656227
Minimum Qty (MOQ):	100
NSN:	5315-00-844-3956
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16562-27 Specifications

Overall Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Diameter:	0.099 Inches Minimum And 0.103 Inches Maximum
Material Thickness:	0.022 Inches Minimum
End Item Identification:	W/s:ssbn Mk-118 Fire Control Sys; Helicopter, Carrier Based Asw, Sh-60f; Consolidated Targets; Trainer, B-1b Aircraft; Helicopter, Mh-53e; Missile, Strategic Air To Ground (sram li); Boilers, 1200 Psi; Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Advance Attack, Ah-1w
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	1000 Double Pound
Material:	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.