



Description

length: 3/8, diameter: 1/8", tubular, slotted, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1656231
Minimum Qty (MOQ):	50
NSN:	5315-00-238-1584
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS16562-31 Specifications

Overall Length:	0.360 Inches Minimum And 0.390 Inches Maximum
Diameter:	0.131 Inches Minimum And 0.135 Inches Maximum
Material Thickness:	0.028 Inches Nominal
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	2100 Double Pound
Material:	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.