

Description


length: 3/4", diameter: 1/8", tubular slotted, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS1656236 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5315-00-810-3701 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



P/N MS16562-36 Specifications

| | |
|---|---|
| Overall Length: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Diameter: | 0.131 Inches Minimum And 0.135 Inches Maximum |
| Material Thickness: | 0.028 Inches Minimum |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Shear Strength: | 2100 Double Pound |
| Material: | Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Slotted |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.