

## Description

length: 7/16", diameter: 1/16", tubular slotted, carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS165625
Minimum Qty (MOQ):	100
NSN:	5315-00-240-1014
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

# P/N MS16562-5 Specifications

Overall Length:	0.423 Inches Minimum And 0.453 Inches Maximum
Diameter:	0.062 Inches Nominal
Material Thickness:	0.012 Inches Nominal
Hardness Rating:	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	425 Double Pound
Material:	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Style Designator:	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.