

Description

MS16562-96 Spring Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS1656296 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5315-00-282-3642 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16562-96 Specifications

| | |
|---|---|
| Overall Length: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Diameter: | 0.062 Inches Nominal |
| Material Thickness: | 0.012 Inches Nominal |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | 66,comp 1070 Thru 1095 Fed Std Single Material Response Overall |
| Surface Treatment: | Phosphate Zinc Overall |
| Surface Treatment Document And Classification: | Mil-c-16232,ty 2 Mil Spec Single Treatment Response Overall |
| Style Designator: | Slotted |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-96> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.