

Description

size: 13/32", basic external, cadmium plated steel, tapered section type, MS16624 series ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166241040
Minimum Qty (MOQ):	50
NSN:	5325-00-252-4721
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates



* See page 2 for technical characteristics

P/N MS16624-1040 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.361 Inches Minimum And 0.368 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	69.5 Rockwell Superficial 30-n Minimum And 73.0 Rockwell Superficial 30-n Maximum
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Surface Treatment:	Cadmium And Chromate Or Chromate Zinc
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3 Or Zinc Plated,mil-c-81562,ty 2 Cl 3

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-1040> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.