



★ FASTENERS

Military-Fasteners.com

P/N MS16624-1062

Description

for shaft size: 5/8", basic external cadmium plated steel, tapered section type, MS16624 series ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166241062
Minimum Qty (MOQ):	50
NSN:	5325-00-803-7305
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16624-1062 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.579 Inches Nominal
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.035 Inches Nominal
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	66.0 Rockwell Superficial 30-n Minimum And 71.0 Rockwell Superficial 30-n Maximum
Material:	Steel Fed Fed-std 66 No. 1066 Thru 1090
Material:	Steel Fed Fed-std 66 No. 1066 Thru 1090
Surface Treatment:	Cadmium And Chromate Or Chromate Zinc
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3 Or Zinc Plated,mil-c-81562,ty 2 Cl 3

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-1062> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.