

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166241212
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-663-1246
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16624-1212 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	1.939 Inches Minimum And 1.979 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.075 Inches Minimum And 0.081 Inches Maximum
<b>Ring Style:</b>	External
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
<b>Material:</b>	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1090
<b>Material:</b>	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-1212> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.