

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS166241231 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5325-00-803-9971 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-1231 Specifications

| | |
|-------------------------------------|--|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 2.114 Inches Minimum And 2.154 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.075 Inches Minimum And 0.081 Inches Maximum |
| Ring Style: | External |
| Usage Design: | External |
| Material Hardness Rating: | 47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum |
| Material: | Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1070 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090 |
| Material: | Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1070 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090 |
| Surface Treatment: | Cadmium And Chromate |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 3 |

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-1231> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.