

Description

MS16624 series ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166241275
Minimum Qty (MOQ):	10
NSN:	5325-00-200-7234
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates



* See page 2 for technical characteristics

P/N MS16624-1275 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	2.513 Inches Minimum And 2.563 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.090 Inches Minimum And 0.096 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
Material:	Steel, Fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Material:	Steel, Fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-1275> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.