

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166242150
Minimum Qty (MOQ):	40 EA
NSN:	5325-00-282-6987
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-2150 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	1.372 Inches Minimum And 1.397 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.048 Inches Minimum And 0.052 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
Material:	Steel,fed,fed Std 66,fs1066 To 1090
Material:	Steel,fed,fed Std 66,fs1066 To 1090
Surface Treatment:	Zinc
Surface Treatment:	Zinc Plated

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-2150> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.