

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                     |
|-------------------------|-------------------------------------|
| SKU / Model:            | MS166242150                         |
| Minimum Qty (MOQ):      | 40 EA                               |
| NSN:                    | 5325-00-282-6987                    |
| Schedule B:             | 7318.29.0000                        |
| ECCN:                   | 9A991                               |
| National Motor Freight: | 063520, Waveguide In Boxes / Crates |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16624-2150 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Cross-sectional Shape Style:</b> | Rectangular   |
| <b>Inside Diameter:</b>             | 1.372 Inches Minimum And 1.397 Inches Maximum       |
| <b>Casehardening Indicator:</b>     | Not Casehardened                                    |
| <b>Major Thickness:</b>             | 0.048 Inches Minimum And 0.052 Inches Maximum       |
| <b>Ring Style:</b>                  | External  |
| <b>Usage Design:</b>                | External  |
| <b>Material Hardness Rating:</b>    | 47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum |
| <b>Material:</b>                    | Steel,fed,fed Std 66,fs1066 To 1090                 |
| <b>Material:</b>                    | Steel,fed,fed Std 66,fs1066 To 1090                 |
| <b>Surface Treatment:</b>           | Zinc  |
| <b>Surface Treatment:</b>           | Zinc Plated   |

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-2150> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.