

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166242150
Minimum Qty (MOQ):	40 EA
NSN:	5325-00-282-6987
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16624-2150 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	1.372 Inches Minimum And 1.397 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.048 Inches Minimum And 0.052 Inches Maximum
<b>Ring Style:</b>	External
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
<b>Material:</b>	Steel,fed,fed Std 66,fs1066 To 1090
<b>Material:</b>	Steel,fed,fed Std 66,fs1066 To 1090
<b>Surface Treatment:</b>	Zinc
<b>Surface Treatment:</b>	Zinc Plated

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-2150> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.