

P/N MS16624-4027

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

 SKU / Model:
 MS166244027

 Minimum Qty (MOQ):
 20

NSN: 5325-00-804-7639

Schedule B: 7318.16.0060

ECCN: 9A991

National Motor Freight: 063520, Waveguide In Boxes / Crates



^{*} See page 2 for technical characteristics

P/N MS16624-4027 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.245 Inches Minimum And 0.252 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting https://military-fasteners.com/rings/retaining+rings/MS16624-4027 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16624-4027 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16624-4027 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16624-4027 and selecting the quantity you want the property of the property o