

## P/N MS16624-4039

### **Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS166244039

Minimum Qty (MOQ): 25

NSN: 5325-00-804-7701

Schedule B: 7318.16.0060

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16624-4039 Specifications

| Cross-sectional Shape Style:          | Rectangular   |
|---------------------------------------|---|
| Inside Diameter:                      | 0.349 Inches Minimum And 0.356 Inches Maximum                                     |
| Casehardening Indicator:              | Not Casehardened  |
| Major Thickness:                      | 0.023 Inches Minimum And 0.027 Inches Maximum                                     |
| Ring Style:                           | External  |
| Usage Design:                         | External  |
| Material Hardness Rating:             | 63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum |
| Material:                             | Steel, Ams 5520   |
| Material:                             | Steel Comp 632  |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response  |
| Surface Treatment:                    | Passivate   |
| Surface Treatment:                    | Passivated, Qq-p-35   |

# **How to Order**

Order this ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16624-4039">https://military-fasteners.com/rings/retaining+rings/MS16624-4039</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="here">here</a> to complete your order.