

## Description


size: 1/2", basic external, corrosion resistant steel, tapered section type

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS166244050
Minimum Qty (MOQ):	20
NSN:	5325-00-804-7645
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates



\* See page 2 for technical characteristics

## P/N MS16624-4050 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	0.456 Inches Minimum And 0.463 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.033 Inches Minimum And 0.037 Inches Maximum
<b>Ring Style:</b>	External
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
<b>Material:</b>	Steel, Ams 5520
<b>Material:</b>	Steel Comp 632
<b>Material Document And Classification:</b>	Ams 5520 Assn Std Single Material Response
<b>Surface Treatment:</b>	Passivate
<b>Surface Treatment:</b>	Passivated, Qq-p-35

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4050> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.