

## P/N MS16624-4056

### **Description**

MS16624-4056 Retaining Ring

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS166244056

Minimum Qty (MOQ): 25

NSN: 5325-00-804-7646

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 063520, Waveguide In Boxes / Crates









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16624-4056 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.511 Inches Minimum And 0.526 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

## **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16624-4056">https://military-fasteners.com/rings/retaining+rings/MS16624-4056</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16624-4056">https://military-fasteners.com/rings/retaining+rings/MS16624-4056</a> and selecting the quantity you