

Description

for shaft size: 5/8", basic external corrosion resistant steel - tapered section type

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166244062
Minimum Qty (MOQ):	10
NSN:	5325-00-753-3699
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS16624-4062 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.569 Inches Minimum And 0.584 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35
Nondefinitive Spec/std Data:	1 Type And 2 Style

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4062> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.