

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | MS166244066 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-634-7446 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 063520, Waveguide In Boxes / Crates |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-4066 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 0.611 Inches Minimum And 0.626 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.033 Inches Minimum And 0.037 Inches Maximum |
| Ring Style: | External |
| Usage Design: | External |
| Material Hardness Rating: | 63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated, Qq-p-35 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4066> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.