

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166244066
Minimum Qty (MOQ):	10
NSN:	5325-00-634-7446
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-4066 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.611 Inches Minimum And 0.626 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4066> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.