

P/N MS16624-4137

Description

Ring part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS166244137

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-808-0891

Schedule B: 7318.16.0060

ECCN: 9A991

National Motor Freight: 063520, Waveguide In Boxes / Crates



^{*} See page 2 for technical characteristics

P/N MS16624-4137 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	1.257 Inches Minimum And 1.282 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.048 Inches Minimum And 0.052 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this ring from our inventory online by visiting https://military-fasteners.com/rings/retaining+rings/MS16624-4137 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.