

Description

MS16624 series ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS166244225 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-364-9428 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS16624-4225 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 2.056 Inches Minimum And 2.096 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.075 Inches Minimum And 0.081 Inches Maximum |
| Ring Style: | External |
| Usage Design: | External |
| Material Hardness Rating: | 44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Cadmium And Chromate |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 2 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4225> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.