

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166244243
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-114-0189
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-4243 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	2.230 Inches Minimum And 2.280 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.075 Inches Minimum And 0.081 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-4243> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.