

## P/N MS16624-5012-1

### **Description**

for shaft size: 1/8", basic external cadmium plated steel, tapered section type

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS1662450121

Minimum Qty (MOQ): 50

NSN: 5325-00-804-6895

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16624-5012-1 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.108 Inches Minimum And 0.114 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.009 Inches Minimum And 0.011 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum And 82.0 Rockwell Superficial 15-n Maximum
Material:	Beryllium Copper, Qq-c-533
Material:	Copper Alloy 170 Or Copper Alloy 172
Material Document And Classification:	Qq-c-533 Fed Spec Single Material Response
Surface Treatment:	Cadmium And Chromate Or Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3 Or Cadmium,mil-c-81562,ty 2,cl 3

## **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16624-5012-1">https://military-fasteners.com/rings/retaining+rings/MS16624-5012-1</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16624-5012-1">https://military-fasteners.com/rings/retaining+rings/MS16624-5012-1</a> and selecting the quantity you