

# P/N MS16624-5018-1

Military-Fasteners.com

#### Description

size: 3/16", basic external, cadmium plated steel, tapered section type, MS16624 series ring

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS1662450181
Minimum Qty (MOQ):	100
NSN:	5325-00-432-3584
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



### P/N MS16624-5018-1 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.164 Inches Minimum And 0.170 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.013 Inches Minimum And 0.017 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum And 82.0 Rockwell Superficial 15-n Maximum
Material:	Beryllium Copper, Qq-c-533
Material:	Copper Alloy 170 Or Copper Alloy 172
Material Document And Classification:	Qq-c-533 Fed Spec Single Material Response
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this retaining ring from our inventory online by visiting <u>https://military-fasteners.com/rings/retaining+rings/MS16624-5018-1</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.