

**Description**

size: 3/16", basic external, cadmium plated steel, tapered section type, MS16624 series ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1662450181
Minimum Qty (MOQ):	100
NSN:	5325-00-432-3584
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N MS16624-5018-1 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	0.164 Inches Minimum And 0.170 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.013 Inches Minimum And 0.017 Inches Maximum
<b>Ring Style:</b>	External
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	77.0 Rockwell Superficial 15-n Minimum And 82.0 Rockwell Superficial 15-n Maximum
<b>Material:</b>	Beryllium Copper, Qq-c-533
<b>Material:</b>	Copper Alloy 170 Or Copper Alloy 172
<b>Material Document And Classification:</b>	Qq-c-533 Fed Spec Single Material Response
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-5018-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.