

Description

MS16624-5019 Retaining Ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166245019
Minimum Qty (MOQ):	100
NSN:	5325-00-445-3244
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16624-5019 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.175 Inches Minimum And 0.181 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.013 Inches Minimum And 0.017 Inches Maximum
Ring Style:	External
Usage Design:	External
Material Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum And 82.0 Rockwell Superficial 15-n Maximum
Material:	Beryllium Copper, Qq-c-533
Material:	Copper Alloy 170 Or Copper Alloy 172
Material Document And Classification:	Qq-c-533 Fed Spec Single Material Response
Surface Treatment:	Phosphate Zinc
Surface Treatment:	Phosphate, Mil-p-16232, Type Z, Class 2

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-5019> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.