

Description


MS16624 series ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS1662450231 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5325-00-806-0198 |
| Schedule B: | 7415.39.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N MS16624-5023-1 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 0.211 Inches Minimum And 0.217 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.013 Inches Minimum And 0.017 Inches Maximum |
| Ring Style: | External |
| Usage Design: | External |
| Material Hardness Rating: | 77.0 Rockwell Superficial 15-n Minimum And 82.0 Rockwell Superficial 15-n Maximum |
| Material: | Beryllium Copper, Qq-c-533 |
| Material: | Copper Alloy 170 Or Copper Alloy 172 |
| Material Document And Classification: | Qq-c-533 Fed Spec Single Material Response |
| Surface Treatment: | Cadmium And Chromate |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 3 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16624-5023-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.