

**Description**

housing diameter: 2", basic internal cadmium plated steel, tapered section type

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS166251200
Minimum Qty (MOQ):	10
NSN:	5325-00-804-2784
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS16625-1200 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	2.147 Inches Minimum And 2.180 Inches Maximum
<b>Major Thickness:</b>	0.059 Inches Minimum And 0.066 Inches Maximum
<b>Ring Style:</b>	Internal
<b>Usage Design:</b>	Internal
<b>Material Hardness Rating:</b>	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
<b>Material:</b>	Steel, fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Material:</b>	Steel, fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-1200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.