

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166251225
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-252-4763
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16625-1225 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	2.460 Inches Minimum And 2.530 Inches Maximum
<b>Major Thickness:</b>	0.075 Inches Minimum And 0.081 Inches Maximum
<b>Ring Style:</b>	Internal
<b>End Item Identification:</b>	W/s: Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Shipboard Material Handling Equipment; Wasp Class Lhd; Teletype, Model 28; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Forrestal Class Cv; Nimitz Class Cvn; Aircraft, Harrier Av-8b; Mk 28, 5-inch 38 Caliber Twin Gun Mount;fms-knox Class Ff
<b>Usage Design:</b>	Internal
<b>Material Hardness Rating:</b>	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
<b>Material:</b>	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Material:</b>	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-1225> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.