

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166251225
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-252-4763
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16625-1225 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	2.460 Inches Minimum And 2.530 Inches Maximum
Major Thickness:	0.075 Inches Minimum And 0.081 Inches Maximum
Ring Style:	Internal
End Item Identification:	W/s: Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Shipboard Material Handling Equipment; Wasp Class Lhd; Teletype, Model 28; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Forrestal Class Cv; Nimitz Class Cvn; Aircraft, Harrier Av-8b; Mk 28, 5-inch 38 Caliber Twin Gun Mount;fms-knox Class Ff
Usage Design:	Internal
Material Hardness Rating:	47.0 Rockwell C Minimum And 52.0 Rockwell C Maximum
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-1225> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.