

## P/N MS16625-3068

### **Description**

MS16625 series ring

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS166253068

Minimum Qty (MOQ): 50

NSN: 5325-00-807-7968

Schedule B: 7318.29.0000

ECCN: 9A991

National Motor Freight: 095190, Hardware, Noi Sub 9



# P/N MS16625-3068 Specifications

Cross-sectional	Rectangular
Shape Style:	
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.758 Inches Minimum And 0.773 Inches Maximum
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	67.5 Rockwell Superficial 30-n Minimum And 72.0 Rockwell Superficial 30-n Maximum
Material:	Steel, Fed Std 66, Comp 1066 Or Steel, Fed Std 66, Comp 1069 Or Steel, Fed Std 66, Comp 1070 Or Steel, Fed Std 66, Comp 1072 Or Steel, Fed Std 66, Comp 1074 Or Steel, Fed Std 66, Comp 1075 Or Steel, Fed Std 66, Comp 1080 Or Steel, Fed Std 66, Comp 1084 Or Steel, Fed Std 66, Comp 1085 Or Steel, Fed Std 66, Comp 1086 Or Steel, Fed Std 66, Comp 1090
Material:	Steel Comp 1566 Or Steel, Fed Std 66, Comp 1069 Or Steel Comp 1070 Or Steel Comp 1572 Or Steel Comp 1074 Or Steel Comp 1075 Or Steel Comp 1078 Or Steel Comp 1080 Or Steel Comp 1070 Or Steel Comp 1085 Or Steel Comp 1086 Or Steel Comp 1090
Material Document And Classification:	Fed Std 66, Comp 1066 Fed Std 1st Material Response And Fed Std 66, Comp 1070 Fed Std 3rd Material Response And Fed Std 66, Comp 1072 Fed Std 4th Material Response And Fed Std 66, Comp 1074 Fed Std 5th Material Response And Fed Std 66, Comp 1075 Fed Std 6th Material Response And Fed Std 66, Comp 1078 Fed Std 7th Material Response And Fed Std 66, Comp 1080 Fed Std 8th Material Response And Fed Std 66, Comp 1084 Fed Std 9th Material Response And Fed Std 66, Comp 1085 Fed Std 10th Material Response And Fed Std 11th Material Response And Fed Std 66, Comp 1090 Fed Std 12th Material Response
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-3068">https://military-fasteners.com/rings/retaining+rings/MS16625-3068</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-3068">https://military-fasteners.com/rings/retaining+rings/MS16625-3068</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-3068">https://military-fasteners.com/rings/retaining+rings/MS16625-3068</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-3068">https://military-fasteners.com/rings/retaining+rings/MS16625-3068</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining-rings/mS16625-3068">https://military-fasteners.com/rings/retaining-rings/mS16625-3068</a> and selecting the part of th