

Description

MS16625-4037 Retaining Ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166254037
Minimum Qty (MOQ):	50
NSN:	5325-00-804-6855
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates



* See page 2 for technical characteristics

P/N MS16625-4037 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.405 Inches Minimum And 0.425 Inches Maximum
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4037> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.