

Description

MS16625-4062 Retaining Ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS166254062

Minimum Qty (MOQ): 25

NSN: 5325-00-807-5332

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16625-4062 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Casehardening Indicator: | Not Casehardened |
| Outside Diameter: | 0.689 Inches Minimum And 0.704 Inches Maximum |
| Major Thickness: | 0.033 Inches Minimum And 0.037 Inches Maximum |
| Ring Style: | Internal |
| Usage Design: | Internal |
| Material Hardness Rating: | 63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated, Qq-p-35 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4062> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.