

**Description**

MS16625 series ring

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166254150
Minimum Qty (MOQ):	10
NSN:	5325-00-530-7953
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates



\* See page 2 for technical characteristics

# P/N MS16625-4150 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.640 Inches Minimum And 1.685 Inches Maximum
Major Thickness:	0.048 Inches Minimum And 0.052 Inches Maximum
Ring Style:	Internal
End Item Identification:	Crane (rt41aa);m1a2 Abrams Tank, 2350-01-328-5964 (eaa Cmbt85pk3);torpedo Systems, Mk 46;submarine Auxillary And Miscellaneous Systems;helicopter, Search And Rescue, Hh-60h;oliver Perry Class Ffg;fms - Knox Class Ff;submarine Hull Structure;helicopter, Carrier Based Asw, Sh-60f;ticonderoga Class Cg (47);spruance Class Dd (963);kidd Class Ddg
Usage Design:	Internal
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4150> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.