

P/N MS16625-4162

Description

MS16625 series ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS166254162

Minimum Qty (MOQ): 25

NSN: 5325-00-263-2667

Schedule B: 7318.16.0060

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









^{*} See page 2 for technical characteristics

P/N MS16625-4162 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.779 Inches Minimum And 1.839 Inches Maximum
Major Thickness:	0.059 Inches Minimum And 0.065 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting https://military-fasteners.com/rings/retaining+rings/MS16625-4162 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16625-4162 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16625-4162 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rings/retaining+rings/MS16625-4162 and selecting the quantity you want of the property of the propert