

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166254168
Minimum Qty (MOQ):	15 EA
NSN:	5325-00-958-9656
Schedule B:	4016.93.1010
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16625-4168 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.849 Inches Minimum And 1.909 Inches Maximum
Major Thickness:	0.059 Inches Minimum And 0.065 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35
Nondefinitive Spec/std Data:	Part No. Ms16625-4168

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4168> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.