

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | MS166254187 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5325-00-598-1340 |
| Schedule B: | 7318.16.0060 |
| ECCN: | 9A991 |
| National Motor Freight: | 063520, Waveguide In Boxes / Crates |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16625-4187 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Casehardening Indicator: | Not Casehardened |
| Outside Diameter: | 2.047 Inches Minimum And 2.107 Inches Maximum |
| Major Thickness: | 0.059 Inches Minimum And 0.065 Inches Maximum |
| Ring Style: | Internal |
| Usage Design: | Internal |
| Material Hardness Rating: | 44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated, Qq-p-35 |

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4187> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.