

**Description**

MS16625 series ring

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166254200
Minimum Qty (MOQ):	5
NSN:	5325-00-530-7960
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates



\* See page 2 for technical characteristics

## P/N MS16625-4200 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	2.185 Inches Minimum And 2.245 Inches Maximum
<b>Major Thickness:</b>	0.059 Inches Minimum And 0.065 Inches Maximum
<b>Ring Style:</b>	Internal
<b>Usage Design:</b>	Internal
<b>Material Hardness Rating:</b>	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
<b>Material:</b>	Steel, Ams 5520
<b>Material:</b>	Steel Comp 632
<b>Material Document And Classification:</b>	Ams 5520 Assn Std Single Material Response
<b>Surface Treatment:</b>	Passivate
<b>Surface Treatment:</b>	Passivated, Qq-p-35

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.