

## P/N MS16625-4262

### **Description**

Retaining Ring part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS166254262
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-550-7961
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS16625-4262 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	2.880 Inches Minimum And 2.950 Inches Maximum
Major Thickness:	0.090 Inches Minimum And 0.096 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

## **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-4262">https://military-fasteners.com/rings/retaining+rings/MS16625-4262</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-4262">https://military-fasteners.com/rings/retaining+rings/MS16625-4262</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-4262">https://military-fasteners.com/rings/retaining+rings/MS16625-4262</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/MS16625-4262">https://military-fasteners.com/rings/retaining+rings/MS16625-4262</a> and selecting the quantity you want the properties of the properti