

## Description

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS166254350
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-781-5874
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS16625-4350 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	3.835 Inches Minimum And 3.945 Inches Maximum
<b>Major Thickness:</b>	0.106 Inches Minimum And 0.112 Inches Maximum
<b>Ring Style:</b>	Internal
<b>Usage Design:</b>	Internal
<b>Material Hardness Rating:</b>	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
<b>Strength Rating:</b>	200000.0 Pounds Per Square Inch Minimum Yield
<b>Material:</b>	Steel, Ams 5520
<b>Material:</b>	Steel Comp 632
<b>Material Document And Classification:</b>	Ams 5520 Assn Std Single Material Response
<b>Surface Treatment:</b>	Passivate
<b>Surface Treatment:</b>	Passivated, Qq-p-35

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4350> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.