

Description

MS16625-4450 Retaining Ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166254450
Minimum Qty (MOQ):	1
NSN:	5325-01-091-1544
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16625-4450 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	4.875 Inches Minimum And 5.005 Inches Maximum
Major Thickness:	0.106 Inches Minimum And 0.114 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16625-4450> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.