

P/N MS16626-4059

Description

Ring part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS166264059
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-059-3115
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N MS16626-4059 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.540 Inches Minimum And 0.555 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	External Inverted Lugs
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this ring from our inventory online by visiting https://military-fasteners.com/rings/retaining+rings/MS16626-4059 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.