

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166264081
Minimum Qty (MOQ):	15 EA
NSN:	5325-00-455-0332
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16626-4081 Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	0.741 Inches Minimum And 0.756 Inches Maximum
Casehardening Indicator:	Not Casehardened
Major Thickness:	0.040 Inches Minimum And 0.044 Inches Maximum
Ring Style:	External Inverted Lugs
Usage Design:	External
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16626-4081> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.