

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS166264087 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5325-00-080-9091 |
| Schedule B: | 7318.15.5030 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS16626-4087 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Inside Diameter: | 0.800 Inches Minimum And 0.815 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Major Thickness: | 0.040 Inches Minimum And 0.044 Inches Maximum |
| Ring Style: | External Inverted Lugs |
| Usage Design: | External |
| Material Hardness Rating: | 44.0 Rockwell C Minimum And 51.0 Rockwell C Maximum |
| Material: | Steel, Ams 5520 |
| Material: | Steel Comp 632 |
| Material Document And Classification: | Ams 5520 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated, Qq-p-35 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16626-4087> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.