

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS166271100
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-687-5158
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS16627-1100 Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.076 Inches Minimum And 1.091 Inches Maximum
Major Thickness:	0.040 Inches Minimum And 0.044 Inches Maximum
Ring Style:	Internal Inverted Lugs
Usage Design:	Internal
Strength Rating:	238000.0 Pounds Per Square Inch Minimum Tensile
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Material:	Steel,fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
Surface Treatment:	Cadmium And Chromate
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 3

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16627-1100> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.