

**Description**

Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS166271100
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-687-5158
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS16627-1100 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	1.076 Inches Minimum And 1.091 Inches Maximum
<b>Major Thickness:</b>	0.040 Inches Minimum And 0.044 Inches Maximum
<b>Ring Style:</b>	Internal Inverted Lugs
<b>Usage Design:</b>	Internal
<b>Strength Rating:</b>	238000.0 Pounds Per Square Inch Minimum Tensile
<b>Material:</b>	Steel, fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Material:</b>	Steel, fed Std 66 Aisi 1066 Or 1069 Or 1070 Or 1072 Or 1074 Or 1075 Or 1078 Or 1080 Or 1084 Or 1086 Or 1090
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 3

## How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS16627-1100> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.